



Product Information Flyer

DESCRIPTION

CENTER SAVER is a waterproof grease recommended for use on ferrous and non-ferrous metals.

APPLICATION

CENTER SAVER is designed as a lubricant for centers on lathes, grinders, hobbing machines, etc. Also lubricates and waterproofs bearings, pumps, and tools. Works well with various metals such as; aluminum, cast iron, carbon steels, high speed steel, high alloy steels, stainless steels and yellow metals. Not recommended for magnesium or magnesium alloys.

FEATURES & BENEFITS

REDUCES WEAR ON CENTERS:

The extreme pressure (EP) lubrication reduces the friction between the workpiece and the center. Prevents seizing of machine tool screws and fixtures.

EASY TUBE APPLICATION:

Quick use and cuts waste.

LONG LASTING:

CENTER SAVER won't run when it gets hot or is under pressure, metalworking fluids won't wash it off and it stays clean.

RECOMMENDED STARTING DILUTIONS

FOR INDUSTRIAL USE ONLY
Use without diluting (100%)

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Grease

Solubility in water: Insoluble

Viscosity (SUS) @ 100°F (37.7°C): NA

pH Concentrate: NA

Total Chlorine/Chloride, wt%: 8.7/<50ppm

Silicones: None

Appearance and Odour: Opaque/Chemical

Weight, lb/gal, 60°F (15.6 °C): 7.5

Flash Point /Sp.Gr./Boiling Point: SEE MSDS

pH Mix 100%, Typical Operating: NA

Total Sulfur, wt%: 0.1

HANDLING and STORAGE

If frozen, thaw completely at room temperature. Inside storage is recommended.

SAFETY DATA SHEET

Available at www.cimcool.ca

For additional information refer to its WHMIS MSDS, website or contact CIMCOOL® Technical Services at 1-513-458-8199 in Ohio or 1-888-254-1919 in Canada.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.