

OAK[®] GREEN-LPH

MAINTENANCE FLOOR CLEANER



Product Information Flyer

DESCRIPTION

OAK GREEN-LPH is a water-based, alkaline floor cleaner with a moderate pH, for use in automatic floor scrubbers on concrete, linoleum or ceramic flooring in manufacturing facilities.

APPLICATION

OAK GREEN-LPH can be applied by floor scrubbers, spray bottles, mop buckets and brushing methods. Not recommended for use with magnesium or alloyed magnesium.

FEATURES & BENEFITS

VERSITILITY:

OAK GREEN-LPH can be used as a floor cleaner to lift insoluble soils such as clay and carbon. It can also be used as a general maintenance cleaner or degreaser.

CONTROLLED FOAMING:

OAK GREEN-LPH enhanced detergency and emulsification controls foam in its applications.

ECONOMICAL:

OAK GREEN-LPH concentrated product can be diluted for low-end use cost.

OPERATOR FRIENDLY:

OAK GREEN-LPH has a pleasant pine scent with no hazardous solvents in its formulation.

RECOMMENDED STARTING DILUTIONS

FOR INDUSTRIAL USE ONLY

OAK GREEN-LPH is to be mixed with water for use. Fluid may be more difficult to mix when water temperature is below 55°F (13°C). Add no other materials to the concentrate or mix unless approved by your CIMCOOL® Territory Manager.

Automatic Floor Scrubbers – Use at 5% (1:20)

Light Duty Cleaning – Use at 2-5% (1:50 to 1:20)

Medium Duty Cleaning – Use at 10% (1:10)

Heavy-Duty Cleaning – Use at 20% (1:5)

NOTE: Rinse thoroughly when using manual cleaning methods. Always spot check solution on painted surfaces before applying.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

Solubility in water: 100% miscible

pH Concentrate: 9.0

pH Mix 5.0%, Typical Operating: 8.7

Appearance and Odor: Clear/mild pine

Weight, lb/gal, 60 °F (15.6 °C): 8.7

Flash Point /Sp.Gr./Boiling Point: SEE MSDS

HANDLING AND STORAGE

If frozen, product separates. Thaw completely at room temperature and stir thoroughly prior to use. Inside storage is recommended.

SAFETY DATA SHEET

Available at www.cimcool.ca

For additional information refer to its WHMIS MSDS, website or contact CIMCOOL® Technical Services at 1-513-458-8199 in Ohio or 1-888-254-1919 in Canada.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.