



Product Information Flyer

DESCRIPTION

PRODUCTO FCR-410 is a water based, heavy-duty rubber lubricant.

APPLICATION

PRODUCTO FCR-410 is intended for use in lubricating rubber or plastic hoses, O-rings and other parts to facilitate assembly. It is recommended for installing large non-flexible hoses and is recommended to minimize residues and possible slippage. Dilution can vary depending on the application.

FEATURES & BENEFITS

RESIDUE:

PRODUCTO FCR-410 dries after application, preventing accidental slippage of parts after assembly. Dried residues are readily soluble in water. This product will not adversely affect rubber or plastics.

EASY TO APPLY:

PRODUCTO FCR-410 can be applied to parts by automated, mechanical or manual methods. Most common manual methods are dip, spray or sponge application.

HANDLING:

PRODUCTO FCR-410 is non-toxic, non-flammable, water based material that requires no special precautions in handling. It allows for easy lubrication of mandrels and spindles for tube and hose application but is slippery when wet so care should be taken when applying.

RECOMMENDED STARTING DILUTIONS

PRODUCTO FCR-410 is to be mixed with water for use. Always add concentrate to water. Add no other materials to the concentrate or mix unless approved by your CIMCOOL® Territory Manager.

For General Assembly: 5% (1:20)

CONCENTRATION

Contact your local CIMCOOL TECHNICAL SPECIALIST OR TERRITORY MANAGER, or you may contact CIMCOOL® Technical Services at 1-513-458-8199.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

Solubility in Water: 100% Miscible

Boiling Point: 212°F (100°C)

pH Concentrate: 7.5

Appearance and Odour: Clear/Chemical

Specific Gravity: 1.03

VOC Content (by ASTM D2369): NA

pH Mix 5%: 7.1

HANDLING and STORAGE

If frozen product separates, thaw completely at room temperature and stir thoroughly. Inside storage is recommended.

SAFETY DATA SHEET

Available at www.cimcool.ca

For additional information refer to its WHMIS MSDS, website or contact CIMCOOL® Technical Services at 1-513-458-8199 in Ohio or 1-888-254-1919 in Canada.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.