

# SAFETY DATA SHEET

# 1. Identification

1. Identification			
Product identifier	CIMPULSE™ 33MP		
	METALWORKING FLUID		
Other means of identification			
SDS number	Not applicable		
Product code	B01896		
Recommended use	METALWORKING FLUID		
<b>Recommended restrictions</b>	None known.		
Manufacturer/Importer/Supplier	/Distributor information		
Company name	CIMCOOL® Industrial Products LLC		
	3000 Disney Street		
	Cincinnati, Ohio 45209		
Telephone (General Information)	513-458-8100		
Emergency telephone number	1-800-424-9300 (CHEMTREC)		
Emergency telephone number (outside USA)	1-703-527-3887 (CHEMTREC)		
Supplier			
Company name	DUBOIS CHEMICAL CANADA INC dba CIMCOOL® Canada		
Address	B1 – 1175 Appleby Line		
	Burlington, ON L7L 5H9 Canada		
Telephone (General Information)	905-319-1919		
Emergency telephone number (outside USA)	1-703-527-3887 (CHEMTREC)		
Supplier	Not available.		
2. Hazard identification			
Physical hazards	Not classified.		
Health hazards	Not classified.		
Environmental hazards	Not classified.		
Label elements			
Hazard symbol	None.		
Signal word	None.		
Hazard statement	The mixture does not meet the criteria for classification.		
Precautionary statement			
Prevention	Observe good industrial hygiene practices.		
Response	Wash hands after handling.		
Storage	Store away from incompatible materials.		
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.		
Other hazards	None known.		
Supplemental information	Use in manufacturing processes only.		

# 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
TRIETHANOLAMINE		102-71-6	10 - 30
Other components below reportable levels			80 - 100

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures	
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist. Under normal conditions of intended use, this material is not expected to be an inhalation hazard.
Skin contact	Rinse skin with water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth thoroughly. Drink 1 or 2 glasses of water. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
General information	If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.

# 5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry powder. Carbon dioxide (CO2). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Not applicable, non-combustible.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Wear suitable protective equipment.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	No unusual fire or explosion hazards noted.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Wear appropriate personal protective equipment. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Local authorities should be advised if significant spillages cannot be contained. This product is miscible in water. Clean up in accordance with all applicable regulations.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

# 7. Handling and storage

**Precautions for safe handling** Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure.

Conditions for safe storage, St including any incompatibilities te

Store in tightly closed container. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use. Store away from incompatible materials (see Section 10 of the SDS).

### 8. Exposure controls/personal protection

US. ACGIH Threshold Lim Components	Туре	Value
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3
Canada. Alberta OELs (Oc Components	cupational Health & Safety Code, Sche Type	edule 1, Table 2) Value
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3
Safety Regulation 296/97,		for Chemical Substances, Occupational Health and
Components	Туре	Value
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3
Canada. Manitoba OELs (F Components	Reg. 217/2006, The Workplace Safety A Type	nd Health Act) Value
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3
,	ontrol of Exposure to Biological or Che Type	emical Agents) Value
TRIETHANOLAMINE (CAS	TWA	3.1 mg/m3
		o i ringinio
102-71-6)		0.5 ppm
102-71-6)	inistry of Labor - Regulation respectin Type	0.5 ppm
102-71-6) Canada. Quebec OELs. (M	inistry of Labor - Regulation respectin Type	0.5 ppm g occupational health and safety)
102-71-6) Canada. Quebec OELs. (M Components TRIETHANOLAMINE (CAS 102-71-6)	inistry of Labor - Regulation respectin Type	0.5 ppm g occupational health and safety) Value 5 mg/m3
102-71-6) Canada. Quebec OELs. (M Components TRIETHANOLAMINE (CAS 102-71-6) Canada. Saskatchewan Of Components TRIETHANOLAMINE (CAS	inistry of Labor - Regulation respectin Type TWA ELs (Occupational Health and Safety R	0.5 ppm g occupational health and safety) Value 5 mg/m3 Regulations, 1996, Table 21)
102-71-6) Canada. Quebec OELs. (M Components TRIETHANOLAMINE (CAS 102-71-6) Canada. Saskatchewan Of Components	inistry of Labor - Regulation respectin Type TWA ELs (Occupational Health and Safety R Type	0.5 ppm g occupational health and safety) Value 5 mg/m3 Regulations, 1996, Table 21) Value
102-71-6) Canada. Quebec OELs. (M Components TRIETHANOLAMINE (CAS 102-71-6) Canada. Saskatchewan OB Components TRIETHANOLAMINE (CAS 102-71-6)	inistry of Labor - Regulation respectin Type TWA ELs (Occupational Health and Safety R Type 15 minute	0.5 ppm g occupational health and safety) Value 5 mg/m3 Regulations, 1996, Table 21) Value 10 mg/m3 5 mg/m3
102-71-6) Canada. Quebec OELs. (M Components TRIETHANOLAMINE (CAS 102-71-6) Canada. Saskatchewan Of Components TRIETHANOLAMINE (CAS 102-71-6) logical limit values propriate engineering	inistry of Labor - Regulation respectin Type TWA ELs (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted fo Good general ventilation should be us applicable, use process enclosures, la maintain airborne levels below recom	0.5 ppm g occupational health and safety) Value 5 mg/m3 tegulations, 1996, Table 21) Value 10 mg/m3 5 mg/m3 or the ingredient(s). sed. Ventilation rates should be matched to conditions. If ocal exhaust ventilation, or other engineering controls to mended exposure limits. If exposure limits have not been
102-71-6) Canada. Quebec OELs. (M Components TRIETHANOLAMINE (CAS 102-71-6) Canada. Saskatchewan Of Components TRIETHANOLAMINE (CAS 102-71-6) logical limit values propriate engineering strols	inistry of Labor - Regulation respectin Type TWA ELs (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted fo Good general ventilation should be us applicable, use process enclosures, la maintain airborne levels below recom established, maintain airborne levels	0.5 ppm g occupational health and safety) Value 5 mg/m3 regulations, 1996, Table 21) Value 10 mg/m3 5 mg/m3 or the ingredient(s). sed. Ventilation rates should be matched to conditions. If ocal exhaust ventilation, or other engineering controls to mended exposure limits. If exposure limits have not been to an acceptable level. Eye wash fountain and emergence
102-71-6) Canada. Quebec OELs. (M Components TRIETHANOLAMINE (CAS 102-71-6) Canada. Saskatchewan Of Components TRIETHANOLAMINE (CAS 102-71-6) logical limit values propriate engineering strols	TWA TWA TWA TUA TWA TUA TWA TUA TUA TUA Type 15 minute 8 hour No biological exposure limits noted for Good general ventilation should be us applicable, use process enclosures, lo maintain airborne levels below recom established, maintain airborne levels showers are recommended. s, such as personal protective equipm	0.5 ppm g occupational health and safety) Value 5 mg/m3 regulations, 1996, Table 21) Value 10 mg/m3 5 mg/m3 or the ingredient(s). sed. Ventilation rates should be matched to conditions. If ocal exhaust ventilation, or other engineering controls to mended exposure limits. If exposure limits have not been to an acceptable level. Eye wash fountain and emergence
102-71-6) Canada. Quebec OELs. (M Components TRIETHANOLAMINE (CAS 102-71-6) Canada. Saskatchewan Of Components TRIETHANOLAMINE (CAS 102-71-6) logical limit values propriate engineering strols	inistry of Labor - Regulation respectin Type TWA ELs (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted for Good general ventilation should be us applicable, use process enclosures, le maintain airborne levels below recom established, maintain airborne levels showers are recommended. s, such as personal protective equipm Wear safety glasses with side shields	0.5 ppm g occupational health and safety) Value 5 mg/m3 tegulations, 1996, Table 21) Value 10 mg/m3 5 mg/m3 or the ingredient(s). sed. Ventilation rates should be matched to conditions. If ocal exhaust ventilation, or other engineering controls to mended exposure limits. If exposure limits have not been to an acceptable level. Eye wash fountain and emergence ent
102-71-6) Canada. Quebec OELs. (M Components TRIETHANOLAMINE (CAS 102-71-6) Canada. Saskatchewan Of Components TRIETHANOLAMINE (CAS 102-71-6) logical limit values propriate engineering strols	inistry of Labor - Regulation respectin Type TWA ELs (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted for Good general ventilation should be us applicable, use process enclosures, le maintain airborne levels below recom established, maintain airborne levels showers are recommended. s, such as personal protective equipm Wear safety glasses with side shields	0.5 ppm g occupational health and safety) Value 5 mg/m3 tegulations, 1996, Table 21) Value 10 mg/m3 5 mg/m3 or the ingredient(s). sed. Ventilation rates should be matched to conditions. If ocal exhaust ventilation, or other engineering controls to mended exposure limits. If exposure limits have not been to an acceptable level. Eye wash fountain and emergence ent
102-71-6) Canada. Quebec OELs. (M Components TRIETHANOLAMINE (CAS 102-71-6) Canada. Saskatchewan Of Components TRIETHANOLAMINE (CAS 102-71-6) logical limit values propriate engineering strols	TwA TWA TWA TWA TLS (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted for Good general ventilation should be us applicable, use process enclosures, lo maintain airborne levels below recom established, maintain airborne levels showers are recommended. s, such as personal protective equipm Wear safety glasses with side shields recommended.	0.5 ppm g occupational health and safety) Value 5 mg/m3 tegulations, 1996, Table 21) Value 10 mg/m3 5 mg/m3 or the ingredient(s). sed. Ventilation rates should be matched to conditions. If ocal exhaust ventilation, or other engineering controls to mended exposure limits. If exposure limits have not been to an acceptable level. Eye wash fountain and emergency ent
102-71-6) Canada. Quebec OELs. (M Components TRIETHANOLAMINE (CAS 102-71-6) Canada. Saskatchewan Of Components TRIETHANOLAMINE (CAS 102-71-6) logical limit values propriate engineering ntrols	inistry of Labor - Regulation respectin Type TWA ELs (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted for Good general ventilation should be us applicable, use process enclosures, la maintain airborne levels below recom established, maintain airborne levels showers are recommended. s, such as personal protective equipm Wear safety glasses with side shields recommended. Nitrile gloves are recommended.	0.5 ppm g occupational health and safety) Value 5 mg/m3 regulations, 1996, Table 21) Value 10 mg/m3 5 mg/m3 or the ingredient(s). sed. Ventilation rates should be matched to conditions. If ocal exhaust ventilation, or other engineering controls to mended exposure limits. If exposure limits have not been to an acceptable level. Eye wash fountain and emergency ent s (or goggles). Do not get in eyes. Eye wash fountain is

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

····) ····	
Appearance	CLEAR
Physical state	Liquid.
Form	Liquid.
Color	Not available.
Odor	CHEMICAL
Odor threshold	Not available.
рН	7.9
Melting point/freezing point	24 °F (-4.4 °C)
Initial boiling point and boiling range	> 212 °F (> 100 °C)
Flash point	Not Applicable
Evaporation rate	Like water when diluted
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	100 % Water Miscible
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
pH in aqueous solution	7.5 @ 5%
Specific gravity	1.058
VOC ASTM D2369	6 %
10. Stability and reactivity	

### 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Do not add sodium nitrite or other nitrosating agents which may form cancer causing nitrosamines. Acids. Oxidizing agents.
Hazardous decomposition products	Smoke, fumes, oxides of nitrogen, and oxides of carbon

# 11. Toxicological information

# Information on likely routes of exposure

Inhalation	Not classified.
Skin contact	Not classified.
Eye contact	Not classified.
Ingestion	Not classified.
Symptoms related to the physical, chemical and	Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

# toxicological characteristics

### Information on toxicological effects

#### Acute toxicity

Components	Species	Test Results
TRIETHANOLAMINE (CAS 102-7	71-6)	
<u>Acute</u>		
Dermal		
Liquid		
LD50	Rabbit	> 2000 mg/kg
Oral		
Liquid		
LD50	Rat	4190 mg/kg
Skin corrosion/irritation	Not classified.	
Serious eye damage/eye rritation	Not classified.	
Respiratory or skin sensitizatio	n	
Canada - Alberta OELs: Irri	tant	
TRIETHANOLAMINE (C. Canada - Quebec OELs: Se	,	Irritant
TRIETHANOLAMINE (C.	AS 102-71-6)	Sensitizer.
<b>Respiratory sensitization</b>	Not a respiratory sensiti	zer.
Skin sensitization	This product is not expe	cted to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not cons	idered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
IARC Monographs. Overall	Evaluation of Carcinoge	nicity
TRIETHANOLAMINE (C	AS 102-71-6)	3 Not classifiable as to carcinogenicity to humans.
Reproductive toxicity	This product is not expe	cted to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Not classified.	
Further information	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.	
12. Ecological information	n	
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.	
Components	Species	Test Results

Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	565.2 - 658.3 mg/l, 48 hours

Components		Species	Test Results
Acute			
Fish	LC50	Bluegill (Lepomis macrochirus)	450 - 1000 mg/l, 96 hours
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.		
Bioaccumulative potential			
Partition coefficient n-octain TRIETHANOLAMINE	nol / water (log	Kow) -2.3	
Mobility in soil	This product	is miscible with water.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
13. Disposal consideratio	ns		
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.		
Local disposal regulations	Dispose in accordance with all applicable regulations.		
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

14. Transport information

Contaminated packaging

TDG

Not regulated as dangerous goods.

#### ΙΑΤΑ

Not regulated as dangerous goods.

#### IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established. Annex II of MARPOL 73/78 and the IBC Code

disposal.

### 15. Regulatory information

**Canadian regulations** This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act Not regulated. Export Control List (CEPA 1999, Schedule 3) Not listed. Greenhouse Gases Not listed. Precursor Control Regulations Not regulated. International regulations Stockholm Convention Not applicable. Rotterdam Convention Not applicable. Kyoto protocol

Not applicable.

**Montreal Protocol** 

Not applicable.

**Basel Convention** 

Not applicable.

### International Inventories

Country(s) or region	Inventory name On inventory or exemption	ot (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates that all compo	nents of this product comply with the inventory requirements administered by the governing country(s)	)

# **16. Other information**

Issue date Revision date Version # NFPA ratings	07-18-2016 07-26-2021 06 Health: 1 Flammability: 0 Instability: 0
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Hazard identification: Response Composition / Information on Ingredients: Component Summary Physical & Chemical Properties: Multiple Properties Ecological information: Mobility in soil