

CIMPULSE™ 51MP



DESCRIPTION

CIMPULSE 51MP is an oil containing metalworking fluid.

APPLICATION

CIMPULSE 51MP is a multi-purpose, moderate-duty fluid for machining and grinding. It offers high performance without the use of traditional extreme pressure lubricants and is recommended for turning, drilling, milling, reaming, boring, tapping, broaching, sawing and grinding for most metals other than magnesium alloys or cast aluminum.

FEATURES & BENEFITS

- For all metals and all operations (see above)
- For use in a wide range of water qualities with exceptional hard water stability
- Does not contain DCHA or triazine
- Machines stay clean and parts are easy to wash

RECOMMENDED STARTING DILUTIONS:

CIMPULSE 51MP is to be mixed with water for use. Always add concentrate to water. Add no materials to the concentrate or mix unless approved by CIMCOOL®.

Machining and Grinding: 5% to 10% (5 – 10 on the refractometer scale)

Refractometer Factor: 1.0 5% Mix pH is typically 9.0

SAFETY DATA SHEET:

Available at www.cimcool.ca

For additional information refer to its SDS, website or contact your local CIMCOOL TERRITORY MANAGER, or CIMCOOL® Technical Services at 1-888-254-1919

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.

CIMCOOL FLUID TECHNOLOGY 3000 DISNEY STREET CINCINNATI, OH 45209 2/2018 PC B01895