



Product Information Flyer

DESCRIPTION

CIMSTAR 10-507VLC is a VALUE-LINE semi-synthetic metalworking fluid.

The VALUE LINE of products offers cost effective alternatives while maintaining good overall performance characteristics.

APPLICATION

CIMSTAR 10-507VLC was developed for use on ferrous and most non-ferrous materials. It can be used on mild steels, stainless steels, hardened steels, exotic materials and most aluminum alloys. It should not be used on magnesium alloys.

FEATURES & BENEFITS

VERSATILE PRODUCT:

For use in moderate to heavy duty operations including sawing yet versatile enough for surface grinding or milling, drilling, cut tapping and turning

Chlorine free technology

CIMCOOL "VALUE-LINE":

Cost effectiveness with CIMCOOL performance

CIMSTAR® 10-507VLC

METALWORKING FLUID

RECOMMENDED STARTING DILUTIONS:

CIMSTAR 10-507VLC is to be mixed with water for use Always add concentrate to water. Fluid may be more difficult to mix when water temperature is below 55°F (13°C). Add no other materials to the concentrate or mix unless approved by your CIMCOOL® Territory Manager.

Grinding	5% - 10%	(1:20 to 1:10)
Machining	5% - 10%	(1:20 to 1:10)

CONCENTRATION

MI Titration, Non-solvent Titration, Total Alkalinity, CIMCHEK™ Test Strip or Refractometer can be used.

The Refractometer Factor is 1.5

Multiply the scale reading obtained on your CIMCOOL® Refractometer by this factor to obtain the mix concentration in percent. Calibrate the refractometer so that it reads 0.0 with water before testing the sample mix. Remove gross contaminants from the sample mixes before testing. A refractometer is only recommended for use when checking the concentration of a fresh charge.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES:

Physical State: Liquid

Solubility in water: 100% miscible

Viscosity (SUS) @ 100°F (38°C): 650

pH Concentrate: 9.8

Total Chlorine/Chloride, wt%: 0.0/<50ppm

Silicones: No

Appearance and Odor: Clear/Chemical

Weight, lb/gal, 60°F (15.6 °C): 8.6

Flash Point /Sp.Gr./Boiling Point: SEE MSDS

pH Mix 5%, Typical Operating: 8.8

Total Sulfur, wt%: 0.3

HANDLING and STORAGE

If frozen thaw completely at room temperature. Inside storage is recommended.

SAFETY DATA SHEET

Available at www.cimcool.ca

For additional information refer to its WHMIS MSDS, website or contact CIMCOOL® Technical Services at 1-513-458-8199 in Ohio or 1-888-254-1919 in Canada.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.



3000 Disney Street
Cincinnati, OH 45209
1-513-458-8199
Fax 1-513-458-8179