CIMCOOL® FLUID TECHNOLOGY

SAFETY DATA SHEET

1. Identification

Product identifier MILFORM® OAK DRAW® 785

STAMPING AND DRAWING FLUID

Other means of identification

SDS number Not applicable

Product code B30192

Recommended use STAMPING AND DRAWING FLUID

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name CIMCOOL® Industrial Products LLC

3000 Disney Street Cincinnati, Ohio 45209

Telephone (General

Information)

513-458-8100

Emergency telephone

number

1-800-424-9300 (CHEMTREC)

Emergency telephone number (outside USA)

1-703-527-3887 (CHEMTREC)

Supplier

Company name Milacron Canada Corp.

Address 1175 Appleby Line Road, Unit B-1

Burlington Ontario L7L5H9 Canada

Telephone (General

Information)

905-319-1919

Emergency telephone number (outside USA)

1-703-527-3887 (CHEMTREC)

2. Hazard identification

Physical hazards Not classified.

Health hazards Serious eye irritation

Environmental hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes serious eye irritation.

Precautionary statement

Prevention Wash thoroughly after handling. Wear eye protection/face protection.

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Category 2

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Material name: MILFORM® OAK DRAW® 785

Version #: 01 Issue date: 08-27-2019

1 / 9

Supplemental information

6.97% of the mixture consists of component(s) of unknown acute oral toxicity. 6.97% of the mixture consists of component(s) of unknown acute dermal toxicity.

Use in manufacturing processes only.

The classified hazards shown on this SDS are associated with the product concentrate. These hazards are not expected under recommended use conditions and dilution.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
TRIETHANOLAMINE		102-71-6	10 - 30
DIPROPYLENE GLYCOL METHYLETHER	L	34590-94-8	5 - 10
TOLYLTRIAZOLE, SODIUM SALT		64665-57-2	1 - 5
Other components below reportabl	e levels		80 - 100

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist. Under normal conditions of

intended use, this material is not expected to be an inhalation hazard.

Rinse skin with water. If skin irritation or rash occurs: Get medical advice/attention. Wash Skin contact

contaminated clothing before reuse.

redness, swelling, and blurred vision.

Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye Eye contact

irritation persists: Get medical advice/attention.

Rinse mouth thoroughly. Drink 1 or 2 glasses of water. Do not induce vomiting. If vomiting occurs, Ingestion

keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if

Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing,

you feel unwell.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

General information If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in

attendance.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Alcohol resistant foam. Dry powder, Carbon dioxide (CO2), Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing

media

Not applicable, non-combustible.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Wear suitable protective equipment.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. In the Specific methods

event of fire and/or explosion do not breathe fumes.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained. This product is miscible in water. Clean up in accordance with all applicable regulations.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use. Do not allow material to freeze. Store away from incompatible materials (see Section 10 of the SDS).

606 mg/m3 100 ppm

5 mg/m3

8. Exposure controls/personal protection

Occupational exposure limits

TRIETHANOLAMINE (CAS

102-71-6)

US. ACGIH Threshold Limit Values

	Туре	Value	
DIPROPYLENE GLYCOL METHYL ETHER (CAS 34590-94-8)	STEL	150 ppm	
	TWA	100 ppm	
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3	
Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)			
	Туре	Value	
DIPROPYLENE GLYCOL METHYL ETHER (CAS 34590-94-8)	STEL	909 mg/m3	
•		150 ppm	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

	Туре	Value	
DIPROPYLENE GLYCOL METHYL ETHER (CAS 34590-94-8)	STEL	150 ppm	
	TWA	100 ppm	
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3	

Canada, Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

TWA

TWA

ounded: Maintoba OLL3 (Reg. 217/2000, The Workplace durity And Health Act)			
	Туре	Value	
DIPROPYLENE GLYCOL METHYL ETHER (CAS 34590-94-8)	STEL	150 ppm	
	TWA	100 ppm	
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3	

Material name: MILFORM® OAK DRAW® 785

SDS Canada

	Туре	Value
DIPROPYLENE GLYCOL METHYL ETHER (CAS 34590-94-8)	STEL	150 ppm
	TWA	100 ppm
TRIETHANOLAMINE (CAS 102-71-6)	TWA	3.1 mg/m3
		0.5 ppm
Canada. Quebec OELs. (Ministry o	f Labor - Regulation เ Type	respecting occupational health and safety) Value
DIPROPYLENE GLYCOL METHYL ETHER (CAS 34590-94-8)	STEL	909 mg/m3
		150 ppm
	TWA	606 mg/m3
TDIETUANOLANDIE (C. C.	 1	100 ppm
TRIETHANOLAMINE (CAS	TWA	5 mg/m3
102-71-6) Canada Saskatchowan OELs (Occ	Sunational Hoolth and	Safety Regulations, 1996, Table 21)
Canada. Saskatchewan CELS (OCC	сирацопат пеаци апо Туре	Value
DIPROPYLENE GLYCOL METHYL ETHER (CAS 34590-94-8)	15 minute	150 ppm
,	8 hour	100 ppm
TRIETHANOLAMINE (CAS 102-71-6)	15 minute	10 mg/m3
	8 hour	5 mg/m3
logical limit values No b	iological exposure limit	s noted for the ingredient(s).
osure guidelines		
Canada - Alberta OELs: Skin desig	•	
DIPROPYLENE GLYCOL METH (CAS 34590-94-8)		Can be absorbed through the skin.
Canada - British Columbia OELs:	-	
DIPROPYLENE GLYCOL METH (CAS 34590-94-8)		Can be absorbed through the skin.
Canada - Manitoba OELs: Skin des	_	
DIPROPYLENE GLYCOL METH (CAS 34590-94-8)		Can be absorbed through the skin.
Canada - Ontario OELs: Skin desig		
DIPROPYLENE GLYCOL METH (CAS 34590-94-8)		Can be absorbed through the skin.
Canada - Quebec OELs: Skin design	•	
DIPROPYLENE GLYCOL METH (CAS 34590-94-8)		Can be absorbed through the skin.
Canada - Saskatchewan OELs: Sk		
DIPROPYLENE GLYCOL METH (CAS 34590-94-8)		Can be absorbed through the skin.
US ACGIH Threshold Limit Values	-	
DIPROPYLENE GLYCOL METH	HYL ETHER	Can be absorbed through the skin.

Appropriate engineering controls

(CAS 34590-94-8)

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is

recommended.

SDS Canada

Skin protection

Nitrile gloves are recommended. Hand protection Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

CLEAR Appearance Physical state Liquid. **Form** Liquid. Color Not available.

CHEMICAL Odor **Odor threshold** Not available.

8.3

< 32 °F (< 0 °C) Melting point/freezing point > 212 °F (> 100 °C) Initial boiling point and boiling

range

Not Applicable Flash point

Evaporation rate Like water when diluted

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

Not available.

(%)

Not available. Explosive limit - lower (%) Not available. Explosive limit - upper (%) Vapor pressure Not available. Vapor density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) 100 % Water Miscible

Not available. Partition coefficient

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature Viscosity** Not available.

Other information

Not explosive. **Explosive properties Oxidizing properties** Not oxidizing. 8.2 @ 30% pH in aqueous solution 1.030 Specific gravity VOC ASTM D2369 9 %

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous No dangerous reaction known under conditions of normal use.

reactions

Material name: MILFORM® OAK DRAW® 785 5/9 Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

Incompatible materialsDo not add sodium nitrite or other nitrosating agents which may form cancer causing nitrosamines.

Acids. Oxidizing agents.

Hazardous decomposition

products

Smoke, fumes, oxides of nitrogen, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

InhalationNot classified.Skin contactNot classified.

Eye contact Causes eye irritation.

Ingestion Not classified.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity

Components Species Test Results

DIPROPYLENE GLYCOL METHYL ETHER (CAS 34590-94-8)

<u>Acute</u>

Dermal

LD50 Rabbit 9.5 g/kg

Inhalation

Vapor

LC50 Rat > 3.35 mg/l, 7 hours

Oral

Liquid

LD50 Rat > 5000 mg/kg

TOLYLTRIAZOLE, SODIUM SALT (CAS 64665-57-2)

<u>Acute</u>

Dermal

Solid

LD50 Rabbit > 2000 mg/kg

Oral

Solid

LD50 Rat 735 - 930 mg/kg

TRIETHANOLAMINE (CAS 102-71-6)

Acute

Dermal

Liquid

LD50 Rabbit > 2000 mg/kg

Oral

Liquid

LD50 Rat 4190 mg/kg

Skin corrosion/irritation Not classified.

Serious eye damage/eye Causes eye irritation.

irritation

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

TRIETHANOLAMINE (CAS 102-71-6) Irritant

Canada - Quebec OELs: Sensitizer

TRIETHANOLAMINE (CAS 102-71-6) Sensitizer.

SDS Canada

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

TRIETHANOLAMINE (CAS 102-71-6) 3 Not classifiable as to carcinogenicity to humans.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity -

Not classified.

repeated exposure **Aspiration hazard**

Not an aspiration hazard.

Chronic effects

Not classified.

Further information

The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Test Results**

DIPROPYLENE GLYCOL METHYL ETHER (CAS 34590-94-8)

Aquatic

Acute

Fish LC50 Fish

> 1000 mg/l, 96 hours

TOLYLTRIAZOLE, SODIUM SALT (CAS 64665-57-2)

Aquatic

Acute

Fish

Crustacea

EC50 Daphnia LC50 Rainbow Trout 280 mg/l, 48 hours 25 mg/l, 96 hours

TRIETHANOLAMINE (CAS 102-71-6)

Aquatic

Crustacea

EC50 Water flea (Ceriodaphnia dubia) 565.2 - 658.3 mg/l, 48 hours

Acute

Fish LC50 Bluegill (Lepomis macrochirus)

450 - 1000 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

DIPROPYLENE GLYCOL METHYL ETHER

1.01

TRIETHANOLAMINE

-2.3 This product is miscible in water.

Other adverse effects

Mobility in soil

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Material name: MILFORM® OAK DRAW® 785

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not established.

the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

16. Other information

Issue date 08-27-2019

Material name: MILFORM® OAK DRAW® 785 8/9

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Version # 01

NFPA ratings Health: 1

Flammability: 0 Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: MILFORM® OAK DRAW® 785

Version #: 01 Issue date: 08-27-2019

9 / 9