# SAFETY DATA SHEET

#### 1. Identification

**Product identifier MILFORM® OAK DRAW® 829-A** 

STAMPING AND DRAWING FLUID

Other means of identification

SDS number Not applicable B30195 **Product code** 

Recommended use STAMPING AND DRAWING FLUID

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name CIMCOOL® Industrial Products LLC

> 3000 Disney Street Cincinnati, Ohio 45209

Telephone (General

Information)

513-458-8100

**Emergency telephone** 

number

1-800-424-9300 (CHEMTREC)

**Emergency telephone** 

number (outside USA)

1-703-527-3887 (CHEMTREC)

Supplier

Milacron Canada Corp. Company name

**Address** 1175 Appleby Line Road, Unit B-1

Burlington Ontario L7L5H9 Canada

Telephone (General

Information)

905-319-1919

**Emergency telephone** number (outside USA) 1-703-527-3887 (CHEMTREC)

**Supplier** Not available.

2. Hazard identification

Not classified. Physical hazards **Health hazards** Sensitization, skin

**Environmental hazards** Not classified.

Label elements



Warning Signal word

**Hazard statement** May cause an allergic skin reaction.

**Precautionary statement** 

Prevention Avoid breathing mist/vapor. Contaminated work clothing should not be allowed out of the

workplace. Wear protective gloves.

IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical Response

advice/attention. Take off contaminated clothing and wash it before reuse.

Storage Store away from incompatible materials.

Material name: MILFORM® OAK DRAW® 829-A SDS Canada 1/9

Category 1

**Disposal** 

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

None known.

Supplemental information

1.2% of the mixture consists of component(s) of unknown acute oral toxicity. 1.2% of the mixture consists of component(s) of unknown acute dermal toxicity. 5.6% of the mixture consists of component(s) of unknown acute inhalation toxicity.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
ALKANES C14-16, CHLORO		63449-39-8	30 - 60
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES		64742-52-5	30 - 60
PETROLEUM SULFONIC ACID, SODIUM SALT		68608-26-4	1 - 5
SODIUM ALKYLARYL SULFONATE		78330-12-8	1 - 5
SODIUM DODECYLBENZENESULFONATE		25155-30-0	0.1 - 1
Other components below reportable	e levels		10 - 30

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist. Under normal conditions of

intended use, this material is not expected to be an inhalation hazard.

redness, swelling, and blurred vision. May cause an allergic skin reaction.

Rinse skin with water. If skin irritation or rash occurs: Get medical advice/attention. Wash Skin contact

contaminated clothing before reuse.

Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical Eye contact

attention if irritation develops and persists.

Ingestion Rinse mouth thoroughly. Do not give liquids. Do not induce vomiting. If vomiting occurs, keep head

low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel

Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing,

Most important

symptoms/effects, acute and

delayed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

Indication of immediate medical attention and special

treatment needed **General information** 

If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in

attendance.

## 5. Fire-fighting measures

Suitable extinguishing media

Foam. Dry chemical powder. Carbon dioxide (CO2). Use extinguishing measures that are

appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing

media

the chemical

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

During fire, gases hazardous to health may be formed.

Special protective equipment

and precautions for firefighters

Wear suitable protective equipment.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. In the Specific methods

event of fire and/or explosion do not breathe fumes.

General fire hazards No unusual fire or explosion hazards noted.

Material name: MILFORM® OAK DRAW® 829-A 

SDS Canada

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Local authorities should be advised if significant spillages cannot be contained. This product is miscible in water. Prevent entry into waterways, sewer, basements or confined areas. Clean up in accordance with all applicable regulations.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions** 

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

# 7. Handling and storage

Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in tightly closed container. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use. Do not allow material to freeze. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

# Occupational exposure limits

**ACGIH** 

	Туре	Value
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	TWA	5 mg/m3

**Biological limit values** 

Appropriate engineering controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

#### Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is

In case of insufficient ventilation, wear suitable respiratory equipment.

recommended.

Skin protection

**Hand protection** Nitrile gloves are recommended.

Other Wear appropriate chemical resistant clothing.

Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

**CLEAR Appearance** 

Material name: MILFORM® OAK DRAW® 829-A SDS Canada 3/9 **Physical state** Liquid. Liquid. **Form** 

Color Not available. **CHEMICAL** Odor **Odor threshold** Not available. Not Applicable Melting point/freezing point < 32 °F (< 0 °C)

Initial boiling point and boiling

range

Not Applicable

450 °F (232.2 °C) Cleveland Open Cup Flash point

**Evaporation rate** Like water when diluted

Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits Flammability limit - lower Not available.

(%)

Flammability limit - upper

(%)

Not available.

Not available. Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Vapor pressure Vapor density Not available.

Relative density Solubility(ies)

> 100 % Water Miscible Solubility (water)

Partition coefficient

Not available.

Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Not explosive. **Explosive properties Oxidizing properties** Not oxidizing. pH in aqueous solution 9.4 @ 20% Specific gravity 1.095 **VOC ASTM D2369** 5 %

## 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Acids. Oxidizing agents.

**Hazardous decomposition** 

products

Smoke, fumes, hydrogen chloride, and oxides of carbon

# 11. Toxicological information

Information on likely routes of exposure

Inhalation Not classified.

Skin contact May cause an allergic skin reaction.

Not classified. Eye contact Not classified. Ingestion

Material name: MILFORM® OAK DRAW® 829-A

SDS Canada 4/9 Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction.

#### Information on toxicological effects

**Acute toxicity** 

Components Species Test Results

ALKANES C14-16, CHLORO (CAS 63449-39-8)

<u>Acute</u>

Dermal

Liquid

LD50 Rabbit > 2000 mg/kg ATE

Oral

Liquid

LD50 Rat > 5000 mg/kg ATE

PETROLEUM SULFONIC ACID, SODIUM SALT (CAS 68608-26-4)

**Acute** 

Dermal

Liquid

LD50 Rabbit 5000 mg/kg

Oral

Liquid

LD50 Rat > 5000 mg/kg ATE

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)

**Acute** 

**Dermal** 

Liquid

LD50 Rabbit > 5000 mg/kg

Inhalation

Mist

LC50 Rat 5.7 mg/l, 4 hours

Oral

Liquid

LD50 Rat > 5000 mg/kg

SODIUM ALKYLARYL SULFONATE (CAS 78330-12-8)

<u>Acute</u>

Dermal

Liquid

LD50 Rabbit > 2000 mg/kg ATE

Oral

Liquid

LD50 Rat > 5000 mg/kg ATE

SODIUM DODECYLBENZENESULFONATE (CAS 25155-30-0)

**Acute** 

**Dermal** 

Solid

LD50 Rabbit 212 - 2000 mg/kg

Rat 2000 mg/kg

Skin corrosion/irritation

Not classified.

Serious eye damage/eye irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

Oil /Distillate meets the EU requirement of less than 3% (w/w) DMSO extract for total polycyclic

aromatic compound (PAC) using IP 346.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful.

The classification for health and environmental hazards is derived by a combination of calculation **Further information** 

methods and test data, if available.

### 12. Ecological information

Contains a substance which causes risk of hazardous effects to the environment. **Ecotoxicity** 

**Test Results** Components **Species** 

ALKANES C14-16, CHLORO (CAS 63449-39-8)

Aquatic

Fish LC50 Bluegill (Lepomis macrochirus) > 0.1 mg/l, 96 hours

Acute

LC50 Fish Bluegill (Lepomis macrochirus) > 0.1 mg/l, 96 hours

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)

Aquatic

Acute

Fish LC50 Fish > 100 mg/l, 96 hours

SODIUM DODECYLBENZENESULFONATE (CAS 25155-30-0)

Aquatic

Crustacea EC50 Water flea (Ceriodaphnia dubia) 3.26 - 14.51 mg/l, 48 hours LC50 Fish Rainbow trout, donaldson trout 3.2 - 5.6 mg/l, 96 hours

(Oncorhynchus mykiss)

No data is available on the degradability of any ingredients in the mixture. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

SODIUM DODECYLBENZENESULFONATE 1.96

Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

Material name: MILFORM® OAK DRAW® 829-A

SDS Canada 

# 14. Transport information

**TDG** 

UN3082 **UN** number

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ALKANES C14-16, UN proper shipping name

CHLORO)

Transport hazard class(es)

9 Class Subsidiary risk Packing group Ш **Environmental hazards** E3

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**IATA** 

**UN** number UN3082

**UN** proper shipping name Transport hazard class(es) Environmentally hazardous substance, liquid, n.o.s. (ALKANES C14-16, CHLORO)

Class 9 Subsidiary risk **Packing group** Ш **Environmental hazards** No. 9L **ERG Code** 

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Not established.

Cargo aircraft only Allowed with restrictions.

**IMDG** 

UN3082 **UN** number

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ALKANES C14-16, **UN** proper shipping name

CHLORO), MARINE POLLUTANT

Transport hazard class(es)

Class 9 Subsidiary risk Ш Packing group

**Environmental hazards** 

Marine pollutant Yes **EmS** F-A, S-F


Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

IATA; IMDG; TDG



SDS Canada 7/9

## Marine pollutant



**General information** IMDG Regulated Marine Pollutant.

# 15. Regulatory information

**Canadian regulations** 

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

## **Controlled Drugs and Substances Act**

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

**Greenhouse Gases** 

Not listed.

**Precursor Control Regulations** 

Not regulated.

# International regulations

## **Stockholm Convention**

Not applicable.

#### **Rotterdam Convention**

Not applicable.

# **Kyoto protocol**

Not applicable.

# **Montreal Protocol**

Not applicable.

#### **Basel Convention**

Not applicable.

#### **International Inventories**

• • • • • • • • • • • • • • • • • • • •		
Country(s) or region	Inventory name On inventory or	exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates that all compor	nents of this product comply with the inventory requirements administered by the governing co	untry(s)

## 16. Other information

Issue date 03-05-2019

Version # 01

Material name: MILFORM® OAK DRAW® 829-A SDS Canada 8/9 NFPA ratings Health: 1

Flammability: 1 Instability: 0

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

**Revision information** This document has undergone significant changes and should be reviewed in its entirety.