CIMCOOL® FLUID TECHNOLOGY

SAFETY DATA SHEET

1. Identification

Product identifier QUANTALUBE® 270XL

METALWORKING FLUID

Other means of identification

SDS number Not applicable Product code B00168

Recommended use METALWORKING FLUID

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name CIMCOOL® Industrial Products LLC

3000 Disney Street Cincinnati, Ohio 45209

Telephone (General

Information)

513-458-8100

Emergency telephone

number

1-800-424-9300 (CHEMTREC)

Emergency telephone number (outside USA)

1-703-527-3887 (CHEMTREC)

Supplier

Company name Milacron Canada Corp.

Address 1175 Appleby Line Road, Unit B-1
Burlington Ontario L7L5H9 Canada

Telephone (General

Information)

905-319-1919

Emergency telephone number (outside USA)

1-703-527-3887 (CHEMTREC)

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazards Serious eye irritation Category 2A

Environmental hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes serious eye irritation.

Precautionary statement

Prevention Wash thoroughly after handling. Wear eye protection/face protection.

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

SDS Canada

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Version #: 02 Revision date: 02-10-2020 Issue date: 06-05-2017 1 / 9

Other hazards None known.

Supplemental information Use in manufacturing processes only.

Container vapor space may contain hydrogen sulfide. May cause respiratory irritation.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
PETROLEUM SULFONIC ACID, SODIUM SALT		68608-26-4	10 - 30
ALCOHOLS, C12-14, ETHOXYLATED PROPOXYLATED		68439-51-0	5 - 10
TRIETHANOLAMINE		102-71-6	5 - 10
4,4-DIMETHYLOXAZOLIDINE		51200-87-4	1 - 5
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC		64742-65-0	1 - 5
Other components below reportable le	evels		60 - 80

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist. Under normal conditions of

intended use, this material is not expected to be an inhalation hazard.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Skin contact Rinse skin with water. If skin irritation or rash occurs: Get medical advice/attention. Wash

contaminated clothing before reuse.

Eye contact Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye

irritation persists: Get medical advice/attention.

Ingestion Rinse mouth thoroughly. Drink 1 or 2 glasses of water. Do not induce vomiting. If vomiting occurs,

keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if

you feel unwell.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

General information If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in

attendance.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder. Use extinguishing

measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Wear suitable protective equipment.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. In the

event of fire and/or explosion do not breathe fumes.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: QUANTALUBE® 270XL

Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained. Use water spray to reduce vapors or divert vapor cloud drift. This product is miscible in water. Clean up in accordance with all applicable regulations.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

ACGIH

Components	Туре	Value	
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)	TWA	5 mg/m3	
US. ACGIH Threshold Limit Values Components	: Type	Value	
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3	
Canada. Alberta OELs (Occupation	nal Health & Safety Code, Sci	nedule 1, Table 2)	
Components	Туре	Value	
	T\A/A	F (0	
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3	
102-71-6) Canada. British Columbia OELs. (0	Occupational Exposure Limit	ร mg/m3 s for Chemical Substances, Occupationa	al Health and
102-71-6)	Occupational Exposure Limit	•	al Health and
102-71-6) Canada. British Columbia OELs. (0 Safety Regulation 296/97, as amen	Occupational Exposure Limit	s for Chemical Substances, Occupationa	al Health and
102-71-6) Canada. British Columbia OELs. (Canada Regulation 296/97, as amen Components TRIETHANOLAMINE (CAS 102-71-6)	Occupational Exposure Limit ded) Type TWA	s for Chemical Substances, Occupationa Value 5 mg/m3	al Health and
102-71-6) Canada. British Columbia OELs. (0 Safety Regulation 296/97, as amen Components TRIETHANOLAMINE (CAS	Occupational Exposure Limit ded) Type TWA	s for Chemical Substances, Occupationa Value 5 mg/m3	al Health and
102-71-6) Canada. British Columbia OELs. (Canada. British Columbia OELs. (Canada. Regulation 296/97, as amen Components TRIETHANOLAMINE (CAS 102-71-6) Canada. Manitoba OELs (Reg. 217	Occupational Exposure Limit ded) Type TWA /2006, The Workplace Safety	s for Chemical Substances, Occupationa Value 5 mg/m3 And Health Act)	al Health and
Canada. British Columbia OELs. (Canada. British Columbia OELs. (Canada. British Columbia OELs. (Canada. Components) Canada. Manitoba OELs (Reg. 217) Components TRIETHANOLAMINE (CAS 102-71-6)	Occupational Exposure Limit ded) Type TWA /2006, The Workplace Safety Type TWA	S for Chemical Substances, Occupational Value 5 mg/m3 And Health Act) Value 5 mg/m3	al Health and
102-71-6) Canada. British Columbia OELs. (Canada. British Columbia OELs. (Canada. Regulation 296/97, as amen Components TRIETHANOLAMINE (CAS 102-71-6) Canada. Manitoba OELs (Reg. 217) Components TRIETHANOLAMINE (CAS	Occupational Exposure Limit ded) Type TWA /2006, The Workplace Safety Type TWA	S for Chemical Substances, Occupational Value 5 mg/m3 And Health Act) Value 5 mg/m3	al Health and
102-71-6) Canada. British Columbia OELs. (Canada. British Columbia OELs. (Canada. Regulation 296/97, as amen Components TRIETHANOLAMINE (CAS 102-71-6) Canada. Manitoba OELs (Reg. 217) Components TRIETHANOLAMINE (CAS 102-71-6) Canada. Ontario OELs. (Control of	Occupational Exposure Limit ded) Type TWA /2006, The Workplace Safety Type TWA *Exposure to Biological or C	Value 5 mg/m3 And Health Act) Value 5 mg/m3 hemical Agents)	al Health and

Material name: QUANTALUBE® 270XL SDS Canada

Issue date: 06-05-2017

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components Value Type TRIETHANOLAMINE (CAS TWA 5 mg/m3

102-71-6)

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components TRIETHANOLAMINE (CAS 15 minute 10 mg/m3 102-71-6)

> 8 hour 5 mg/m3

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Do not get in eyes. Wear safety glasses with side shields (or goggles). Eye wash fountain is Eye/face protection

recommended.

Skin protection

Hand protection Nitrile gloves are recommended. Other Wear suitable protective clothing.

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

CLEAR Appearance Physical state Liquid. **Form** Liquid.

Color Not available. Odor **CHEMICAL Odor threshold** Not available. Not Applicable Ηq < 5 °F (< -15 °C) Melting point/freezing point Initial boiling point and boiling Not Applicable

range

295 °F (146.1 °C) Flash point

Like water when diluted **Evaporation rate**

Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Material name: QUANTALUBE® 270XL

Not available.

Not available. Explosive limit - lower (%) Not available. Explosive limit - upper (%) Vapor pressure Not available.

Vapor density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) 100 % Water Miscible

4/9

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Not available. **Viscosity**

Other information

Explosive properties Not explosive. Fire point 320 °F (160 °C) Flash point class Combustible IIIB **Oxidizing properties** Not oxidizing. pH in aqueous solution 8.6 @ 5% Specific gravity 1.032 VOC ASTM D2369 6 %

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. **Chemical stability**

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials. May react with corroding cast, gray,

nodular, or other high iron containing swarf or chips to form potentially hazardous levels of

hydrogen sulfide.

Acids. Oxidizing agents. Do not add sodium nitrite or other nitrosating agents which may form Incompatible materials

cancer causing nitrosamines.

Hazardous decomposition

products

Smoke, fumes, oxides of nitrogen, oxides of sulfur, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

Health injuries are not known or expected under normal use. Inhalation Skin contact Health injuries are not known or expected under normal use.

Causes eye irritation. Eye contact

Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity

Components **Species Test Results**

4,4-DIMETHYLOXAZOLIDINE (CAS 51200-87-4)

Acute Dermal Liquid

LD50

Rabbit 970 - 2000 mg/kg

Inhalation

Mist

LC50 Rat 11.66 mg/l, 60 minutes

Oral Liquid

LD50 Rat 956 mg/kg

Material name: QUANTALUBE® 270XL SDS Canada Components **Species Test Results**

ALCOHOLS, C12-14, ETHOXYLATED PROPOXYLATED (CAS 68439-51-0)

Acute Dermal

Liquid

LD50 Rabbit > 2000 mg/kg ATE

Oral Liquid

LD50 Rat > 2000 mg/kg

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)

Acute Dermal

Liquid

LD50 Rabbit > 3000 mg/kg

Oral Liquid

LD50 Rat > 5000 mg/kg

PETROLEUM SULFONIC ACID, SODIUM SALT (CAS 68608-26-4)

Acute Dermal Liquid

LD50 Rabbit

5000 mg/kg

Oral

Liquid

LD50 Rat > 5000 mg/kg ATE

TRIETHANOLAMINE (CAS 102-71-6)

Acute Dermal Liquid

LD50 Rabbit > 2000 mg/kg

Oral Liquid

LD50 Rat 4190 mg/kg

Health injuries are not known or expected under normal use. Skin corrosion/irritation

Serious eye damage/eye

Causes eye irritation.

irritation

Respiratory or skin sensitization Canada - Alberta OELs: Irritant

> TRIETHANOLAMINE (CAS 102-71-6) Irritant

Canada - Quebec OELs: Sensitizer

TRIETHANOLAMINE (CAS 102-71-6) Sensitizer.

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Oil /Distillate meets the EU requirement of less than 3% (w/w) DMSO extract for total polycyclic

aromatic compound (PAC) using IP 346.

IARC Monographs. Overall Evaluation of Carcinogenicity

TRIETHANOLAMINE (CAS 102-71-6) 3 Not classifiable as to carcinogenicity to humans.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Material name: QUANTALUBE® 270XL SDS Canada 6/9 Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

Prolonged inhalation may be harmful. May be harmful if absorbed through skin. **Chronic effects**

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

Further information The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Test Results Components Species

4,4-DIMETHYLOXAZOLIDINE (CAS 51200-87-4)

Aquatic

Acute

Crustacea EC50 Daphnia 45 mg/l, 48 hours ECHA

Fish LC50 Bluegill (Lepomis macrochirus) 59 mg/l, 96 hours

ALCOHOLS, C12-14, ETHOXYLATED PROPOXYLATED (CAS 68439-51-0)

Acute

EC50 Bacteria > 1000 mg/l

Aquatic

Acute

Crustacea EC50 Daphnia > 1 mg/l, 48 hours ATE LC50 Fish Ide, silver or golden orfe (Leuciscus 1 - 10 mg/l, 96 hours

idus)

TRIETHANOLAMINE (CAS 102-71-6)

Aquatic

Crustacea EC50 Water flea (Ceriodaphnia dubia) 565.2 - 658.3 mg/l, 48 hours

Acute

LC50 Bluegill (Lepomis macrochirus) 450 - 1000 mg/l, 96 hours Fish

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

4,4-DIMETHYLOXAZOLIDINE 0.73 ALCOHOLS, C12-14, ETHOXYLATED PROPOXYLATED 1 - 4 **TRIETHANOLAMINE** -2.3

Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

Material name: QUANTALUBE® 270XL

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

SDS Canada

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Not established. Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

16. Other information

Issue date 06-05-2017 02-10-2020 **Revision date**

Version # 02

Material name: QUANTALUBE® 270XL 8/9

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

NFPA ratings Health: 1

Flammability: 1 Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: QUANTALUBE® 270XL SDS Canada

Version #: 02 Revision date: 02-10-2020 Issue date: 06-05-2017