

MILPRO[®] R & O SPINDLE OILS



MILPRO[®] R & O Spindle Oils

Premium grade oils for use in high speed spindle applications.

DESCRIPTION

MILPRO[®] RO 10 and RO 22 are low viscosity R & O oils (rust and oxidation) that are designed to be used in tight tolerance high speed spindle applications. They are thermally stable and provide excellent corrosion protection, water demulsibility and are low foaming, even at high speeds.

These products can also be used in compressors, and circulating systems.

PRODUCT	ISO GRADE	TYPICAL Viscosity, SUS at 100°F	FLASH POINT °F	POUR POINT °F
MILPRO [®] RO 10	10	55	200 min	-22
MILPRO [®] RO 22	22	100	200 min	-22

MILPRO RO Oils are recommended to be used in accordance with good machine maintenance and hygiene practices. They are formulated with high quality base stocks and utilize zinc free additives.

SAFETY DATA SHEET:

Available at www.cimcool.ca

For additional information refer to its SDS on www.cimcool.ca website, or contact your local CIMCOOL[®] Technical Service Specialist or you may contact CIMCOOL Technical Services at 1-888-254-1919.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.

CIMCOOL FLUID TECHNOLOGY
3000 DISNEY STREET
CINCINNATI, OH 45209



MILPRO[®] RO10 is B02017, MILPRO[®] RO22 is B02018
3/2018